PENTAX Digital Cameras Optio Z10







The smallest Paparazzo in the world.

- > The "Z" of this new product series stands for zoom. And everything revolves around the zoom with this camera. Zoom range: 38-266mm
- > New "Intelligent Zoom" function. Unless you're making 24x30cm enlargements then the maximum resolution of the camera isn't needed. Very often a resolution that is sufficient for 10x15cm prints is all you need. At the lower resolution the remaining pixels can be used to extend the zoom range by a factor of up to 16.3x for loss-free images. Combined with the digital zoom this can give you an astounding maximum focal length of 1,350mm!
- > "Digital Wide" for demanding wide-angle photographs. Two single shots are combined by a unique camera function and stored as a 28mm wide-angle photograph.
- > A special protection cover that also serves as the main On/Off switch - offers optimal protection for the high-performance lens.
- > With its extended focal length range the Optio Z10 is suitable for sport photography as well as snapshots. And the speed of operation makes it a joy to carry.
- > To keep your valuable shots blur-free the camera offers an effective digital "Shake Reduction" function.
- > With the automatic face recognition function the Z10 can recognize up to 15 faces in the picture and make the necessary settings for the perfect exposure.
- > The large and brilliant monitor with a 170° viewing angle offers the best viewing characteristics thanks to "IPS Technology", making a bright view possible from extreme angles.



Optio Z10 Code No.	SILVER	19325
Barcode	0027075130685	
Optio Z10 Code No.	Black	19476
Barcode	0027075134980	

Standard Accessories





AC Cabel D-CO24E







Hand strap O-ST20





Software S-SW70



Code No. 39613

AC mains adapter K-AC63E

Optional accessories

Code No. 50170

Leather case LC-Z1



Code No. 39657

Charging Kit K-BC72E

Leather Strap O-ST24



CCD

- 8.29 Megapixel total
- 8.0 Megapixel effective 1/2.5" Interline Transfer CCD with primary colour filter
- Resolution: 8 MP (3,264x2,448), 5 MP (2,592x1,944),
 MP (3,264x2,448), 5 MP (2,592x1,944),
 - 4 MP (2,304×1,728), 3 MP (2,048×1,536), 2 MP (1,600×1,200), 1,024×768, 640×480
- Sensitivity: automatic, manual selectable (ISO 64, 100, 200, 400, 800, 1,600, 3,200)

Lens

- 6.3-44.1mm/3.5~5.4 (38-266mm in 35mm film format)
 12 elements in 9 groups (2 double-sided aspherical lens elements, 2 single-sided aspherical lens elements)
- 7x optical zoom, 5.1x digital zoom
- For photographs with a less than maximum resolution (8.0 megapixels) the "Intelligent Zoom" uses the unused pixels to extend the zoom range
 - 5MP 8.8x, 4MP 9.9x, 3MP 11.2x, 2MP - 14.3x, 1MP - 22.3x and 0.6MP - 35.7x

Monitor

- 2.5" TFT Monitor, approx. 230,000 pixels
- Image viewing on playback: Single image with histogram, 8X magnification, 9 image thumbnail view, "Face Playback", slide show, image rotation

Image formats

- Photo: JPEG (Exif 2.2), DCF, DPOF
- Video: AVI (Motion JPEG), with sound
- Sound: WAV (PCM, mono)

Memory

- SD card
- SDHC card
- approx. 52.MB internal memory

Focus

- 9-Point TTL Contrast Detection System, focus set by various Picture Modes, Spot AF, manual focus and Panfocus
- Photo
 Normal: 0.4m -∞ (wide angle)
- Macro: 0.08m-0.5m (wide angle) Landscape: ∞

Metering

- Multi-field TTL metering, switchable between Multi-field, Centre weighted or Spot metering
- Programme controlled electronic Shutter speed range: approx 1/1,440-4 sec.
- Recording modes: Video, Sound, Digital "Shake Reduction", Auto Pict., Programmed automatic, Night scene, Landscape, Flowers, Natural Skin Tones, Portrait, Children, Sport, Surf & Snow, Food, Pets, Jewellery
- "Face Priority" for Portrait, Natural Skin Tone and Children modes
- Exposure compensation: ±2 EV (1/3 EV steps)

Flash

- Built-in flash with automatic operation in poor lighting conditions
- Manual flash-on and flash-off modes, Soft Flash
- Preflash for reduction of the "Red Eye" effect
- Flash range at ISO Auto
- Wide angle: approx. 0.16-5.4m
- Tele: approx. 0.3-4.0m

Video**

- Resolution: 640 × 480, 320 × 240
- Edit Function: save as photo, individual sequence or multiple scenes spliced together
- Movie "Shake Reduction" for blur-free videos
- Frame rate: 30fps or 15fps (with sound)

Power requirements

- Rechargeable Li-Ion battery D-LI72
- Battery capacity: approx. 180 pictures*
 - approx. 150 min. playback
- AC mains adapter (optionally available)

Interface

- AV (compatible with NTSC and PAL)
- USB 2.0 connection (high speed)
- AC mains connection

Drive modes

- Single, continuous (Standard and High Speed), Self-timer (2 or 10 sec.)
- White balance: Automatic or manual, Daylight, Tungsten, Cloudy, Neon

Playback functions

- Digital and colour filters, Frame composite, Slideshow,
- Enlargement, Trimming, Image & Sound Copy, Image Rotation

Special features

- World time for 75 cities, 25 time zones
- Menu languages: English, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Polish, Portuguese, Russian, Swedish, Spanish, Turkish, Chinese, Japanese Korean, Thai
- Clock function with "OK" button

Operation speeds

- Switch on to ready: 1.4sec.
- Shutter delay: 0.03sec.
- Automatic "Noise Reduction" at shutter speeds longer than 1sec.

Print functions

 PictBridge compatible for single print, print all and DPOF Print, PRINT Image Matching III

System requirements

- PC: Windows 2000 and XP Home Edition/Professional (compatible with Windows Vista)
- CPU: Pentium III 500MHz or newer
- RAM: minimum 128MB
- Available hard drive capacity: minimum 50MB
- Mac: OS 9.2 (with latest version CarbonLib)
 - or higher with QuickTime 6.0
- CPU: POWER Macintosh Processor with minimum 266MHz
- RAM: minimum 8MB,
- Available hard drive capacity 6 MB

Software

 ACDSee for PENTAX, with image data bank, Stitcher and image editing programme

Additional information at www.pentax.co.uk

* Recording capacity shows approximate number of shots recorded during CIPA compliant testing. Actual performance may vary according to operating conditions. Tests conducted using the monitor and flash for 50% of shots.
**Videos cannot be shown on Macintosh computers.

As of 01.09.2007. All data reserved and can be changed without notice.

