
PENTAX Digital Cameras

Optio E60

Code No. Optio E60 SILVER 17291 Barcode 0027075144668 Code No. Optio E60 BLACK 17296 Barcode 0027075144682





















Make the blink of an eye a great moment

- > 10.1 Megapixel resolution for images of optimal photographic quality - and for outstanding cropped enlargements and posters.
- > PENTAX zoom lens with high-quality optical glass lens, 3 aspherical lens elements, with 3X optical (32-96mm in 35mm film format) and 5.7X digital zoom.
- > Video function recorded in 640x480 resolution at 30 fps and with sound recording.
- > Automatic face identification (Face Recognition) for perfectly exposed and focused people shots.
- > Good pictures should be a snap with a modern camera but many pictures still fail due to blurring. With digital Shake Reduction great shots can be had even under poor lighting
- > Particularly good battery management enables up to 620 shots with one set of lithium AA batteries - a previously unheard of
- > 16 shot series continuous shooting mode can record up to 16 consecutive images (640x480 resolution) in a 2-second burst. The perfect solution to analysing high-speed sports.
- > Picture modes analyze the scene presented and automatically select the optimal exposure program.

Packing data

Dimensions (LxWxH): 180x140x80mm

Weight: 625g







Standard Accessories







USB/AV Cable I-UAV77

Hand strap O-ST62

2x AA batteries



Software S-SW81

Optional Accessories







Nylon case NC-E1

Neopren case NC-U1

AC mains adapter K-AC62E





TECHNICAL DATA

Additional information at www.pentax.co.uk

CCD

- 1/2.33" CCD with 10.7 MP total and 10.1 MP effective
- Resolution Photo:

10MP, 7MP, 5MP, 3MP, 2.1MP (16:9), 1024, 640 x 480

• Sensitivity: automatic, manual selectable (ISO 100-6,400)

- 5.7-17.1mm/f2.9~5.2 (32-96mm in 35mm format) 7 elements in 6 groups, 3 aspherical lens elements
- 3x optical zoom
- 5.7x digital zoom
- Intelligent Zoom up to 17.1x

Monitor

• 2.4" TFT Monitor, 100% image view, approx. 112,000 dots

Image formats

• Photo: JPEG (Exif 2.2), DCF

• Video: AVI (Motion-JPEG), with sound

• Sound: WAV (mono)

Memory

• SD-/SDHC card

• Approx. 6.3 internal memory

• TTI Contrast Detection System

• 3 field or Spot AF, Pan Focus, focus tracking for moving subjects

• Normal: 0.5m-∞ Macro: 0.1-0.6m

Metering

• TTL multi segment metering

• Programme controlled electronic shutter Shutter speed range: approx 1/2,000 - 1/4sec.

• Recording modes: Video, Sound, Auto Pict., Programmed automatic, Night scene, Landscape, Flowers, Portrait, Nightscene portrait, Children, Sport, Surf & Snow, Food, Pets, Jewellery, Panorama

• Face Priority with automatic face recognition available in all modes of operation

• Exposure correction: ±2 EV (1/3 EV steps)

Flash

• Built-in flash with automatic operation in poor lighting conditions

• Manual Flash-on and Flash-off modes

• Preflash for reduction of the "Red Eve" effect

• Flash range approx. (at ISO Auto): Wide angle: approx. 0.1-6.0m Tele: approx. 0.35-3.2m

Video

• Resolution: 640x480, 320x240 pixels

• Frame rate: 30fps or 15fps

• Movie Shake Reduction for blur-free video clips

Sound

Power requirements

• 2x AA batteries (Alkaline, Lithium, Nickel and rechargeable Ni-MH with minimum 2,500 mAh)

• Battery capacity: (Lithium / Alkaline batteries) approx. 300 / 200 images* approx. 750 / 280 min. playback*

• AC mains adapter (optionally available)

Connections

- AV (compatible with NTSC and PAL)
- USB 2.0 connection (high speed)
- · AC mains connection

Recording Parameters

- Single, continuous, Video, Self-timer (2 or 10 sec.), 16 shot series in 2 secs. (640 x 480)
- · White balance: Automatic

Playback functions

• Image viewing on playback: single image with histogramme, 10X magnification, 9 image thumbnail view, slide show, image rotation, calendar

Internal editing

• Digital filter, frame function, image size adjust, image and sound copying, "Red Eye Reduction", Portrait Zoom, recalling deleted

Special functions

- Menu languages: English, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Swedish, Spanish, Turkish, Chinese, Japanese, Korean, Thai
- Intelligent Zoom is available when taking images at less than maximum resolution (10.1 Megapixels). The camera uses utilizes the unused pixels to increase zoom range up to 17.1x.
- \bullet Face recognition function (Face Recognition AF & AE) up to 10 faces are recognized - available in all modes of operation
- Inclusion of recording date in the image (i.e. for on-screen presentation)

Readiness delay

• Shutter delay: 0.14sec.

Print functions

• PictBridge compatible for single print, print all and DPOF Print, PRINT Image Matching III

System requirements

• PC: Windows Vista, Windows XP, Windows 2000

Pentium III or newer

RAM: minimum 512MB

Available hard drive capacity: minimum 1 GB

Other conditions: CD Rom drive, Internet Explorer 5.0 (or newer), DirectX 9.0 (or newer), Windows Media Player 9.0 (or newer)

• Mac: OSX (10.3-10.5)

Power Macintosh 233 MHz (or newer)

RAM: minimum 8 MB

Available hard drive capacity minimum 6 MB

Other conditions: CD Rom drive, Quick Time 4.0 (or newer)

Software

- ACDSee for PENTAX
- Image data bank
- Image editing programme
- Slide show
- Stitcher
- Print programme with various page layouts

We recommend Energizer batteries.



As of 24.07.2008. Data subject to change without notice. .



^{*} Recording capacity shows approximate number of shots recorded during CIPAcompliant testing. Actual performance may vary according to operating conditions. Tests conducted using the monitor and flash for 50% of shots.