



PENTAX Digital Cameras

Optio T10

Code No. Optio T10 19081

Barcode 0027075118713



Take photos. Paint pictures. Bring the two together.

- > Large 1/2.5" CCD with 6 Megapixel resolution
- > PENTAX Motor Zoom with high quality glass lens elements and 3x optical and 4x digital zoom
- > Huge 3" TFT Monitor with Touch Display where all camera functions can be selected with a touch of the finger
- > With the Stylus Pen your photos can be worked on immediately and individualised with a choice of existing or new icons. You can also use the Stylus Pen to add written comments to the picture
- > Extensive functions and features, for example, manipulation of images directly on the monitor



Packaging data

Dimensions: 187x162x98mm

Weight: 800g

Standard Accessories

AV Cable I-AVC7 (B)	Code No. 39553
USB Cable I-USB17	Code No. 39233
AC Cable D-CO2E	Code No. 39475
Battery Charging Station D-BC8	Code No. 39122
Li Ion Battery D-LI8	Code No. 39121
Stylus Pen O-SP45	Code No. 39329
Hand Strap O-ST20	Code No. 39195
Software S-SW45	



AV Cable I-AVC7 (B)



USB Cable I-USB17



AC Cable D-CO2E



Battery Charging Station D-BC8



Li Ion Battery D-LI8



Hand Strap O-ST20



Software S-SW45

Optional Accessories

Leather case LC-T1	Code No. 50128
AC Mains Adapter Kit K-AC7E	Code No. 39127
Battery Charging Kit K-BC8E	Code No. 39151
IR Remote Control E (with zoom function)	Code No. 37376
IR Remote Control (without zoom function)	Code No. 37377
Sport Strap O-ST30	Code No. 39270
Leather Strap O-ST24	Code No. 39263



Leather case LC-T1




AC Mains Adapter Kit K-AC7E



Battery Charging Kit K-BC8E



IR-Remote Control



Sport Strap O-ST30



Leather Strap O-ST24

TECHNICAL DATA

CCD

- 6.37 Megapixel – total
6.0 Megapixel – effective
1/2.5" Interline Transfer CCD with Primary Colour Filter
- Resolution: 6 MP (2,816x2,112), 5 MP (2,560x1,920),
4 MP (2,304x1,728), 3 MP (2,048x1,536),
2 MP (1,600x1,200), 640x480
- Colour depth: 3x12 Bit
- Sensitivity: automatic, manual selectable
(ISO 80, 160, 320, 400)

Lens

- smc 6.2–18.6 mm/2.7~5.2 (37.5–112.5 mm in 35mm format)
6 elements in 5 groups (2 double-sided aspherical elements)
- 3x optical zoom
- 4x digital zoom

Monitor

- 3" TFT Monitor, approx. 230,000 pixels, Touch Display Technology with 100% image view

Image formats

- Photo: JPEG (Exif 2.2), DCF, DPOF, PRINT Image Matching III
- Video: AVI (Motion JPEG), with Sound
- Sound: WAV (mono)

Memory

- SD Card
- approx. 23 MB internal memory

Focus

- 5 Point TTL Contrast Detection System, switchable to Landscape (∞), Spot-AF and manual focus
- Normal: 0.4 m – ∞
- Macro: 0.15–0.5m (wide angle)
- Landscape: ∞
- Pan focus: 1.1m – ∞ (wide angle)
4.5m – ∞ (tele)
- Manual: 0.15m – ∞ (wide angle)
0.4m – ∞ (tele)
- Focus limit off: 0.15m – ∞ (wide angle)
0.4m – ∞ (tele)

Exposure

- TTL metering, switchable between Multi-field, Centre weighted or Spot
- Programme controlled electronic shutter
Shutter speeds: approx. 1/2,000–4 sec.
- Programmed Automatic, Picture Modes: Night scene, Video, Sound, Landscape, Flowers, Portrait, Sport, Surf & Snow, Food, Pets
- Exposure correction: ± 2 EV (1/3 steps)

Flash

- Built-in automatic flash with automatic operation in poor lighting conditions.
- Manual on and off
- Preflash for reduction of the "Red Eye" effect
- Flash range (at ISO Auto)
Wide angle: approx. 0.15–4.5m
Tele: approx. 0.4–2.5m

Video

- Resolution: 640x480, 320x240, in 3 quality levels
- Editing functions: Save as photo, scene splitting or scene splicing
- Frame rate: 30 or 15 fps.

Power

- Rechargeable Li Ion Battery D-LI8
- Battery capacity: approx. 130 shots*
approx. 50 min. recording
approx. 90 min. playback
- AC Mains Adapter (optionally available)

Connectivity

- AV (compatible with NTSC and PAL)
- USB connection
- AC mains connection

Shooting modes

- Single, series, self timer (2 or 10 sec.),
IR Remote Control (0 or 3 sec. release delay)
- White balance: Automatic or manual. Daylight, incandescent, shade, neon

Special functions

- World time for 71 cities, 28 time zones
- Menu languages: English, French, German, Spanish, Portuguese, Italian, Swedish, Dutch, Russian, Korean, Chinese, Thai, Japanese
- The operation of the camera is made completely on the touch-sensitive 3"-monitor. Whether setting the parameters for the photograph or image editing, everything is done with a simple touch of the finger.

Print functions

- PictBridge compatible for single printing or print all and DPOF print

System requirements

- PC: Windows 98SE, ME, 2000 and XP Home Edition/Professional
CPU: Pentium III 500 MHz or newer
RAM: minimum 128 MB
Available hard drive capacity: minimum 50 MB
- Mac: OS 9.2 (with latest version CarbonLib) or higher with QuickTime 6.0
CPU: POWER Macintosh processor with minimum 266 MHz
Memory capacity: minimum 8 MB, free hard drive space minimum 6 MB

Software

- ACDSsee for PENTAX, with Image Data Bank, Stitcher and image editing program

Further information at www.pentax.co.uk

*Recording capacity shows approximate number of shots recorded during CIPA-compliant testing. Actual performance may vary according to operating conditions. Tests conducted using the monitor and flash for 50% of shots.