

WG-M2


ACTION CAM

| Color | Art. Code | EAN Code |
|--------|-----------|---------------|
| Orange | 03802 | 0027075296183 |
| Silver | 03814 | 0027075296282 |

SUPPLIED ACCESSORIES

Rechargeable Li Battery D-LI68 - 39063
 Power Adapter D-PA164E - 30218
 PENTAX USB Cable I-USB157 - 37019
 Lens Protector O-LP1631
 Underwater Lens Protector O-LP1632

OPTIONAL ACCESSORIES



ADVANTAGES

Waterproof and shockproof without housing

- ✓ Tough construction (separate housing not required)
- ✓ Waterproof to assure worry-free shooting at a depth of 20m
- ✓ Shock-resistant from a 2m fall
- ✓ Coldproof down to -10°C

High quality Video and Photo

- ✓ 4K Video 3840x2160, 30p with high bit rate of 100Mbps
- ✓ Stereo sound
- ✓ 204° Extra wide-angle lens: 1.6mm (eq. 9.0mm in 35mm), Brightness: F2.0
- ✓ Movie SR (Shake Reduction)
- ✓ Shooting modes: Underwater, Burst shooting, Time-Lapse Movie, Extended Movie Recording, High Speed Movie
- ✓ Optimum white balance in underwater shooting
- ✓ High Speed Continuous Shooting up to 10 fps
- ✓ HDMI Terminal

Ease of use

- ✓ Built-in 1.5" LCD screen, ideal for framing and viewing videos
- ✓ LCD orientation function
- ✓ Intuitive operation
- ✓ Compact and light weight body

Connectivity and sharing

- ✓ Built-in Wi-Fi for camera control, transfer and viewing of the photos from your smartphone or tablet
- ✓ Sharing of videos and photos directly on social networks

Versatility in all sports and activities

- ✓ Full range of accessories for outdoor fixtures to fit all situations

Dimensions: Approx. 57.4 (W)×34.1 (H)×77.8 (D)mm

Weight: 114g (body only)

CAMERA TYPE

| | |
|------|-----------------------------------|
| Type | Action Camera for movie and photo |
|------|-----------------------------------|

SENSOR

| | |
|---|---|
| Number of pixels | Approx. 8 megapixels - effective |
| Sensor size | 1/2.3" CMOS |
| Sensitivity (Standard Output Sensitivity) | Still: ISO AUTO /AUTO-Hi /200 /400 /800 /1600 /3200 /6400 Movie: ISO AUTO /AUTO-Hi |
| Motion Blur Reduction | Electronic image stabilization (Movie SR) *1 |
| White Balance | Auto, Auto (Outdoor), Manual |

*1 Usable in Angle of View «Narrow» at movie. Angle of view to be reduced when Movie SR is on.

FILE FORMATS

| | |
|---------------------------|---|
| Still | JPEG (conforms to Exif 2.3), conforms to DCF2, PRINT Image Matching III |
| Movie | MPEG-4 AVC / H.264 (MOV) |
| Number of Recorded pixels | Still: (4:3) 8M: 3264x2448, 5M: 2592x1944, (16:9) 6M: 3264x1840, 4M: 2592x1464, (1:1) 6M 2448x2448 Movie: 4K (3840x2160: 30fps), Full HD (1920x1080: 60fps/30fps) HD (1280x720: 120fps/60fps/30fps) |
| Quality Level | Still: Fixed (Fine), Movie: S. Fine / Fine *2 |
| Audio | PCM system, stereo sound |
| Storage Media | microSD / microSDHC / microSDXC Memory Card |
| Built-in memory | Approx. 68MB |

*2 Fixed at "Fine" except Movie mode

LENS

| | |
|--|--|
| Focal Length | 1.6mm (approx. 9.0mm in 35mm format equivalent) |
| Maximum Aperture | F2.0 |
| Construction | 8 elements in 8 groups (6 aspherical elements) *3 |
| Field of view | Wide, Medium, Narrow, Underwater |
| Maximum angle of view | Still image: Angle of view Wide: approx. 202° Angle of view Narrow: approx. 150° Movie: Angle of view Wide: approx. 204° Angle of view Narrow: approx. 151° |
| Lens protector / Underwater lens protector | In order to guarantee the waterproof and dustproof performance, please make sure to attach the lens protector to the camera all the time. Waterproof performance is guaranteed only when the camera is equipped with the underwater lens protector O-LP1632. |

*3 The camera is equipped with the Lens Protector O-LP1631.

LCD DISPLAY

| | |
|------------|--|
| Type | 1.5 inch LCD |
| Resolution | Approx. 115,000 dots |
| Editing | Save as Still Image, Divide Movies, Image Copy |

FOCUSING

| | |
|-------------|-----------------|
| Type | Autofocus |
| Focus Range | 0.2m - infinity |

EXPOSURE CONTROL

| | |
|--------------------|--|
| Metering System | Multi Segment / Spot metering |
| Exposure control | Program AE |
| EV Compensation | +/- 2EV (1/2 EV steps) |
| Image Effect Modes | Bright, Natural, Monochrome, Shading, Bleach Bypass, Bold Monochrome, High Contrast *4 |

*4 At Still, Underwater Still Image, or Burst Shooting, only Bright, Natural or Monochrome is selectable.

SHOOTING FEATURES

| | |
|-------------------|--|
| Shooting modes | Still Image, Underwater Still Image, Burst shooting; Movie, Underwater Movie, Time-Lapse Movie, Extended Movie Recording, High Speed Movie |
| Shutter Speed | 1/24000 - 1/4 sec. |
| Burst Shooting | 8fps up to approx. 10 frames |
| High Speed Movie | 4K (3840x2160: 30fps), Full-HD (1920x1080: 60fps/30fps), HD (1280x720: 120fps/60fps/30fps) |
| Shooting Settings | Angle of View (Wide, Narrow), LCD Orientation,(0°,180°,90°,270°), Wind Suppression(On, Off), Vibration(On, Off) |

SPECIAL

| | |
|-------------|---|
| Waterproof | 20m: Equivalent to IPX8 / JIS Class 8 waterproof |
| Shockproof | 2.0m: Conforming to Method 516.5-Shock of the MIL-Standard 810F |
| Dustproof | IP6X / JIS Class 6 dustproof capabilities |
| Freezeproof | -10°C |
| Languages | English, French, German, Spanish, Portuguese, Italian, Dutch, Japanese, Danish, Swedish, Finnish, Polish, Czech, Hungarian, Turkish, Greek, Russian, Thai, Korean, Chinese (Simplified and Traditional) |

POWER SUPPLY

| | |
|--------------|---|
| Power Source | Rechargeable lithium-ion battery D-LI68 |
| Battery life | Still: approx. 450 pictures (using the rechargeable lithium-ion battery) *5 Movie recording: approx. 80 minutes (4K, Fine Settings) *6 Playback: approx. 160 minutes *6 |

*5 Recording capacity shows approximate number of shots recorded during CIPA-compliant testing.

Actual performance may vary depending on operating conditions.

*6 According to the result of RICOH IMAGING in-house testing.

INTERFACES

| | |
|--------------------|---|
| Interfaces | USB2.0 (Micro B), HDMI output terminal (Type D) |
| Wireless interface | Standard: 802.11b/g/n Frequency: 2.4GHz band Security: WPA2 |

DIMENSIONS AND WEIGHT

| | |
|------------|--|
| Dimensions | Approx. 57.4 (W)×34.1 (H)×77.8 (D)mm (excluding the operation parts and protrusion) |
| Weight | Approx. 136g (including battery, microSD memory card and Lens protector O-LP1631) Approx. 114g (excluding battery, microSD memory card and Lens protector O-LP1631) |

ACCESSORIES

Rechargeable lithium-ion battery, Power adapter, USB cable, Lens protector, Underwater lens protector