



The most compact digital high-end camera for snapshot, travel and street. GR system extension now with 40 mm focal length

	ART. CODE	EAN
RICOH GR IIIx Urban Edition	01157	0027075304512

GR IIIx Urban Edition Special Limited Kit

Inspired by the asphalt of big-city streets, and the lights of the sky and neon that reflect in them, the RICOH GR IIIx "Urban Edition" is offered in a metallic gray body color. This elaborately designed surface not only looks particularly classy, it also ensures a pleasant and secure grip feeling. In addition to the special housing color, the blue lens ring is an external feature of this series.

The GR IIIx Urban Edition, is offered as a Special Limited Kit in an edition of 2,000 pieces worldwide. It includes, in addition to the camera in the special body finish, a blue lens ring, a leather wrist strap with a blue application and a black metal hot shoe cover with the engraving: "Since 1996".

Newly developed 26.1mm GR lens

Due to high demand, the GR IIIx is offered with a 26.1mm F2.8 lens (equivalent to 40 mm in 35 mm format) and offers:

- The focal length of 40 mm corresponds to the angle of view of the human eye
- Natural shooting perspective
- More creative possibilities with the bokeh
- The new lens construction results in improved image quality, which is especially noticeable in the peripheral area
- Wide focal length range through adapters and crop functions between 40 and 105 mm

APS-C sensor unit with Sensor Shift Shake Reduction

- 24.24 MP CMOS sensor
- AA filter-free design for best possible sharpness and detail resolution
- 3-axis Shake Reduction, for 4 stops of exposure reliability
- Reduced risk of camera shake due to shock, vibration or movement
- Sensor dust cleaning function

Image-Control function

- 10 different settings for film simulation; now with monotone
- Individual settings of the image look can be stored in the image control

High resolution touch screen monitor

- High-resolution 3.0-inch LCD monitor with approx. 1,037,000 pixels
- Intuitive camera control through operation on the touch-sensitive camera monitor
- Air gapless design reduces reflections and allows working on the monitor even in direct sunlight
- Colour and brightness of the image on the monitor can be adjusted individually
- Specially hardened glass surface protects against scratches and damage

Mobile communication via Bluetooth® and W-LAN

- Wireless connection to mobile devices such as smartphones or tablets
- Newly developed image sync application, now with image size reduction
- Fast and direct upload to social networks
- Bluetooth® connection enables camera control via mobile phone
- Images can be tagged with GPS data
- Built-in stereo microphone

Kit Accessories

RECHARGEABLE BATTERY DB-110	37838	027075300378
POWER ADAPTER		
USB CABLE I-USB166	37822	027075300330
HAND STRAP		
RING CAP GN-2 (BLACK)	30491	0027075304055
METAL-HOTSHOE COVER		



Optional Accessories

BATTERY CHARGER BJ-11	37861	0027075300385
EXTERNAL VIEW FINDER GV-3 (40MM)	37828	0027075303973
LENS ADAPTER GA-2	37826	0027075303935
75MM CONVERSION LENS GT-2	37827	0027075303966
SOFT CASE GC-11	30485	0027075303997
SOFT CASE GC-12	30486	0027075304000
RICOH STRAP ST-2	174790	
RICOH STRAP GS-2	173381	
RICOH STRAP GS-3	175810	0026649758102
METAL HOTSHOE COVER GK-1	30252	0027075300569
RING CAP GN-2 (DARK GREY)	30492	0027075304062
RING CAP GN-2 (BRONZE)	30494	0027075304086
AC ADAPTER KIT K-AC166E	38371	027075301030
RICOH CABLE SWITCH CA-3	30004	027075295650

Packaging

RICOH GR IIIx URBAN EDITION SPECIAL LIMITED KIT

PACK SIZE	142 (B) x (H) 100 x (L) 178,mm
WEIGHT	647 gr

RICOH GR IIIx

MODEL DESCRIPTION

TYPE Compact camera with fixed focal length

IMAGE CAPTURE UNIT

TYPE Primary color filter CMOS. Size: 23.5mm x 15.6mm
 EFFECTIVE PIXELS Approx. 24.24 mega pixels
 TOTAL PIXELS Approx. 24.79 mega pixels
 SENSITIVITY ISO100~102400: Auto, Manual:
 (ISO Auto Lower/Upper Limit and Minimum Shutter Speed can be set)
 4 EV steps
 Sensor-shift shake reduction (SR) (3-axis: Pitch, Yaw, Roll)
 Image stabilization
 AA FILTER SIMULATOR Moiré reduction using SR unit (Off, Low, High)
 DUST REMOVAL Image sensor cleaning using ultrasonic vibrations "DR II"
 WHITE BALANCE Auto White Balance, Multi Auto White Balance, Daylight, Shade, Cloudy, Fl. - Daylight Color, Fl. - Daylight White, Fl. - Cool White, Fl. - Warm White, Tungsten, CTE, Manual White Balance, Color Temperature
 Fine Adjustment: Adjustable ±4 steps on A-B axis or G-M axis
 Highlight Correction, Shadow Correction
 Slow Shutter Speed Noise Reduction, High-ISO Noise Reduction

FILE FORMATS

STILL
 File Format: RAW (DNG) 14bit, JPEG (Exif 2.3), DCF2.0 compliant
 Color Space: sRGB, AdobeRGB
 RECORDED PIXELS [3:2]L(24M:6000x4000), M(15M:4800x3200), S(7M:3360x2240), XS(2M:1920x1280)
 [1:1]L(16M:4000x4000), M(10M:3200x3200), S(5M:2240x2240), XS(1.6M:1280x1280)
 MOVIE
 File Format: MPEG4 AVC/H.264 (MOV)
 RECORDED PIXELS Full HD (1920x1080, 60p/30p/24p), Sound: Built-in stereo microphone
 RECORDING TIME Up to 25 minutes or 4GB; automatically stops recording if the internal temperature of the camera becomes high
 STORAGE MEDIA SD/SDHC/SDXC Memory Card (Conforms to USH-I standards)
 BUILT-IN MEMORY Approx. 2GB

LENS

FOCAL LENGTH 26.1mm
 35MM FORMAT EQUIVALENT Approx. 40mm
 DIGITAL CROP Crop1: 50mm (15MP), Crop2: 107mm (with adapter)(7.5MP)
 APERTURE F2.8~F16
 CONSTRUCTION 7 elements in 5 groups (2 aspherical lens elements)
 MACRO RATIO 0.25x

AUTO FOCUS SYSTEM

TYPE Hybrid AF (Image plane phase-matching and Contrast detection)
 FOCUS MODE Auto-area AF, Zone AF, Select AF, Pinpoint AF, Tracking AF, Continuous AF, MF, Snapshot to pre-selected areas (1m, 1.5m, 2m, 2.5m, 5m), ∞
 FOCUS RANGE Normal: Approx. 0.1m~∞, Macro Mode: Approx. 0.06m~0.12m
 FACE DETECTION ON, Use only in Auto-area, OFF
 AF ASSIST LAMP Available: Built-in LED AF assist light

LCD MONITOR

TYPE 3.0 inch TFT color LCD (aspect ratio 3:2), Approx. 1037K dots, Wide viewing angle, Air-gapless tempered glass
 TOUCH SCREEN Capacitive sensing method
 ADJUSTMENTS Brightness, Saturation, Blue/Amber, Green/Magenta, Outdoor View Setting: ±2 Steps
 MAGNIFICATION Display magnification (4x, 16x), Grid display (4x4 Grid, 3x3 Grid), Histogram, Bright area warning, Electronic Level

EXPOSURE CONTROL

METERING RANGE 0~22EV (ND-AUTO)
 STARTUP TIME 0.8s
 RELEASE TIME lag 30ms
 EXPOSURE MODE Program AE, Aperture Priority AE, Shutter Priority AE, Manual Exposure
 METERING SYSTEM Multi-segment, Center-weighted, Spot, Highlight-weighted, programme line for depth of field priority and maximum aperture priority
 SHUTTER SPEED 1/4000 sec. - 30 sec. (Limit by aperture setting F2.8: 1/2500 - 1/4000 sec.), Timed Exposure (10sec. - 20min.), Bulb, Time
 SHUTTER TYPE Lens Shutter
 EV COMPENSATION Still Image: ±5EV, 1/3EV steps, Movie: ±2EV, 1/3EV steps
 ND FILTER AUTO, ON, OFF

SHOOTING FUNCTIONS

DRIVE MODES Single Frame Shooting, Continuous Shooting, Bracketing, Multi-exposure, Interval Shooting, Interval Composite
 SELF TIMER 10 sec., 2 sec., OFF
 MULTI-EXPOSURE Composite mode: Additive/Average/Bright, Save interim images: OFF/Unblended/Blended/Unblended+Blended
 SHOOTING MODES Interval Shooting: Interval: Min, 1sec. - 60min., Number of shots: ∞, 2-99 times, Start Interval: Now/ Set Time
 Interval Composite: Shooting period: ∞, 10min. - 24hour, Start Interval: Now/Set Time, Save Interim images: OFF/Unblended/Blended
 HORIZON CORRECTION SR On: correction up to 1 degrees, SR Off: correction up to 1.5 degrees

FLASH

BUILD-IN FLASH not available
 HOT SHOE Compatible with P-TTL Auto Flash of actual PENTAX FLASH Lineup
 FLASH SYNC SHUTTER SPEED All shutter speeds
 FLASH MODE Flash On, Flash On+Red-eye, Slow-speed Sync, Slow, Sync+Red-eye Flash
 Exposure Compensation: -2.0 -+1.0

CAPTURE SETTING

IMAGE CONTROL Standard, Vivid, Monotone, Soft Monotone, Hard Monotone, Hi-Contrast B&W, Positive Film, Bleach Bypass, Retro, HDR Tone, Custom1, Custom2
 ADJUST PARAMETERS Saturation, Hue, High/Low Key Adjustment, Contrast, Contrast (Highlight), Contrast (Shadow), Sharpness, Shading, Clarity, Toning, Filter Effect, HDR Tone Level (Adjust parameter varies depending on the selected image setting)

MOVIE

FILE FORMAT MPEG4 AVC/H.264 (MOV)
 RECORDED PIXELS Full HD (1920x1080, 60p/30p/24p)
 RECORDING TIME Up to 25 minutes or 4GB; automatically stops recording if the internal temperature of the camera becomes high
 SOUND Built-in stereo microphone
 EV COMPENSATION ±2EV, 1/3EV steps
 WHITE BALANCE FOR MOVIE Auto White Balance, Daylight, Shade, Cloudy, Fl. - Daylight Color, Fl. - Daylight White, Fl. - Cool White, Fl. - Warm White, Tungsten, CTE, Manual White Balance, Color Temperature
 IMAGE CONTROL FOR MOVIE Standard, Vivid, Monotone, Hard Monotone, Hi-Contrast B&W, Positive Film, Bleach Bypass, Retro, HDR Tone, Custom1, Custom2

PLAYBACK

PLAYBACK FUNCTIONS Playback View: Single frame, Multi-image (20, 48 frames), Display magnification (up to 16x, 100% view and Quick Zoom view available), Histogram (Y histogram, RGB histogram), Grid display (3x3 Grid, 4x4 Grid), Bright area warning, Auto Image Rotation, Base Parameter Adjustment: Brightness, Saturation, Hue, Contrast, Sharpness
 RAW DEVELOPMENT RAW Development: Aspect Ratio, JPEG Recorded Pixels, Color Space, White Balance, Image Control, Peripheral Illumination Correction, Sensitivity, High-ISO Noise Reduction, Shadow Correction
 EDIT Edit: Resize, Cropping, Levels Adjustment, White Balance Adjustment, Color Moiré Correction, Movie Edit (Cut), Movie Edit (Divide)
 PARAMETER ADJUSTMENT Brightness, Saturation, Hue, Contrast, Sharpness
 RAW DEVELOPMENT Aspect Ratio, JPEG Recorded Pixels, Color Space, White Balance, Image Control, Peripheral Illumination Correction, Sensitivity, High-ISO Noise Reduction, Shadow Correction
 EDIT Resize, Cropping, Levels Adjustment, White Balance Adjustment, Color Moiré Correction, Movie Edit (Cut), Movie Edit (Divide)

CUSTOMIZATION

USER MODE Save setting (Max 3 settings can be saved), Rename setting, Recall setting, Delete setting
 FOLDER NAME Date (100_1018,101_1019...) or User assigned folder name (Default "RICOH")
 FILE NAME "R0*****" or User assigned file name File name numbering: Sequential, Reset
 CUSTOMIZE CONTROLS M Mode Dial Setting, ADJ Mode Setting, Fn Button Setting, Shutter Release Button Setting, 4-way Controller Action, Shutter Release Button Confirmation, LCD Touch Operation, Touch AF
 CUSTOMIZE DISPLAY Shooting Information Display Setting, Playback Information Display Setting, Instant Review, Zoom Review, Focus Magnification, Grid Guide type, Electronic Level type, Flicker Reduction
 LANGUAGES English, French, Germany, Spanish, Portuguese, Italy, Dutch, Danish, Swedish, Finnish, Polish, Czech, Hungarian, Turkey, Greek, Russian, Thai, Korean, Simplified Chinese, Traditional Chinese, Japanese
 NEW ACCESSORY External viewfinder for 40mm (KB equivalent) 75mm conversion lens GT-2 (requires lens adapter GA-2)

MOBILE COMMUNICATION

WIRELESS LAN FUNCTION For easy pairing with mobile devices such as smartphones and tablet computers. By installing the dedicated Image Sync application on a mobile device, the user can display a Live-View image on the device's monitor, release the shutter and send various commands from the device. The wireless LAN connection also makes it easy to upload captured images onto SNS sites.
 STANDARDS IEEE 802.11b/g/n (HT20) (Wireless LAN standard protocol)
 FREQUENCY (Center Frequency) 2412MHz~2462MHz (1ch~11ch)
 SECURITY Authentication: WPA2, Encryption: AES

BLUETOOTH®

FUNCTION Camera can be activated and establish wireless LAN connection even though it is in the Sleep Mode. By connecting with the Image Sync app the location data obtained by the smartphone can be recorded onto captured images.
 STANDARDS Bluetooth® v4.2 BLE (Bluetooth Low Energy)
 FREQUENCY (Center Frequency) 2402MHz~2480MHz (CH0~CH39)

POWER SUPPLY

POWER SOURCE Rechargeable Battery DB-110
 AC ADAPTER AC Adapter Kit K-AC166(Optional)
 BATTERY LIFE Number of recordable images: Approx. 200 images, Tested in compliance with CIPA standard. Actual results may vary depending on the shooting condition.
 Playback time: Approx. 180 minutes
 * The playback time is a guide based on RICOH's measurement method
 With USB-C Adapter cable camera interanal

INTERFACES

USB TYPE-C™ Battery Recharge/Power Supply (Optional AC Adapter required), Data Transfer: MTP, Video output: DisplayPort over USB-C (DisplayPort Alternative Mode)

OPERATING ENVIRONMENT

TEMPERATURE 0°C ~ 40°C
 HUMIDITY 85% or less (no condensation)

DIMENSIONS & WEIGHT

DIMENSIONS Approx. 109.4(W)×61.9(H)×35.2(D)mm (excluding protrusions)
 WEIGHT Approx. 262g (Included dedicated battery and SD memory card), Approx. 232g (Body only)

SYSTEM REQUIREMENTS

PC Windows® 7, Windows® 8.1, Windows® 10
 MAC Mac OS X 10.8, 10.9, 10.10, 10.11, 10.12, 10.13